

# Industrial Suspended/Surface Mount LEDE Select 150W High Bay

P700



## SPECIFICATIONS

<b>DIMENSIONS</b>	D340 x H110mm
<b>COLOUR TEMP</b>	4000K Natural White
<b>LUMENS</b>	77W / 14,000lm 96W / 17,000lm 111W / 19,500lm 132W / 23,000lm <b>150W / 25,500lm (default factory setting)</b>
<b>CRI</b>	80
<b>LIFESPAN</b>	50,000 hours (L70 B50) @ 50°C Ambient
<b>BEAM ANGLE</b>	90°
<b>MATERIAL</b>	Aluminium / PC
<b>IP RATING</b>	IP65
<b>IK RATING</b>	IK08
<b>DRIVER</b>	Incorporated, modular quick release plug and play driver pre-wired with 1500mm lead and three pin plug.
<b>FLICKER</b>	≤ 3% at 100Hz, Pst≤1.0; SVM ≤4 at Full Load to avoid stroboscopic effect in rotating machinery
<b>APPLICATION</b>	Industrial Highbay
<b>POWER FACTOR</b>	>0.90
<b>AMBIENT TEMP</b>	-30°C to +50°C
<b>WEIGHT</b>	2600g
<b>WARRANTY</b>	5 Year Warranty

**<25,500**  
LUMENS

**<150**  
WATTS

**AC**  
240V

## AVAILABLE IN

DESCRIPTION	CODE
4000K, Non-sensor, "Select" 5 lumen Adjustable Output Non-Dimmable driver pre-wired with 3 pin plug.	P700 4KNS

Remote sensor version available soon (Code: P700 4KA)

## ACCESSORIES

DESCRIPTION	CODE
250mm Chain with Snap links	P458 CH
Surface Mount Bracket	P700 SMB

## P700 INRUSH CURRENT 50A SURGE TIME 400µs

MCB Type	MCB B10	MCB B16	MCB B20	MCB B25	MCB C10	MCB C16	MCB C20	MCB C25
Max. connected lights	3	5	6	7	6	9	12	14