



Satisfy Professional's Needs

# Corded and Cordless LED Worklight DML805



Powered by both

# AC and DC



# Twenty 0.5W white-light LEDs deliver bright and even light.



## Powered by both...



## Optional accessories



### Makita tripod

Up to two DML805's can be mounted.  
Height : 992-1,750mm  
Set Screw : M8  
Part No. GM0001381



### Vise


Use for mounting DML805 on a scaffolding pipe, etc.  
Set Screw : M8  
Part No. GM0001396



## Battery capacity warning function

automatically notifies the user about reduction in battery capacity by reducing the brightness of light in the following steps.  
Only one LED is on as drawn below. (This will continue about 13 minutes in case of using battery BL1815N.)

1. Full brightness, with all twenty LEDs on
2. Only one LED is on as drawn below. (This will continue about 10 minutes in case of using battery BL1815.)
3. All twenty LEDs turn off.



### All twenty LEDs on



### Only one LED is on



		Light source		
	Illuminance (lx)	Luminous flux (lm)		Type
High	1,150	High 750		LED
Low	750	Low 450		20x 0.5W

## Continuous use

	BL1815N	BL1830	BL1840	BL1850	BL1415	BL1430
Low	5.0h	10h	13h	17h	3.0h	6.0h
High	2.5h	5.0h	6.5h	8.5h	1.5h	3.0h
Charging time	15min	22min	36min	45min	15min	22min
	DC18RC 					

## Corded and Cordless LED Worklight

### DML805 AC or 18V, 14.4V



**Dimensions (L x W x H)** 214x261x328mm (8-3/8"x10-1/4"x12-7/8")  
**Net weight\*** 2.3kg (5.2lbs) with BL1415  
2.6kg (5.8lbs) with BL1850

\*weight according to EPTA-Procedure 01/2003  
Battery and charger are sold separately.

Items of standard equipment and specifications may vary by country or area.



**Makita New Zealand Ltd.**  
15 Orbit Drive, Mairangi Bay  
PO Box 100 914, North Shore, Auckland 0745  
Fax 0800 600 601 Sales 09 479825

Visit our website for information and tool features :  
[www.makita.co.nz](http://www.makita.co.nz)