

**XGT** 40V max

**UNMATCHED MAXIMUM HEAT**

UP TO **600°C**  
MAXIMUM  
TEMPERATURE  
ADJUSTABLE BY 10° INCREMENTS

**MULTI-FUNCTION  
LCD DISPLAY**  
FOR TEMP AND FAN-  
SPEED ADJUSTMENT

UP TO **200 L/M**  
MAX AIR  
FLOW

HG001G



**DHG181**


550°C

**HG001G**


600°C

**MAX TEMPERATURE**
**TEMPERATURE ADJUSTMENT**
**MAX AIR VOLUME**
**CONTINUOUS RUN TIME**
**LOCK ON FUNCTION**
**WEIGHT (WITH BATTERY)**
**WEIGHT (SKIN)**
**DIMENSIONS (LxWxH)**

 50°C - 550°C  
**6 STAGE DIAL**

 50°C - 600°C  
**WITH 10°C INCREMENTS**

120 / 200 L/Min

120 / 150 / 180 / 200 L/Min

 550°C / 200L/Min **BL1860B: 21 Min**

 600°C / 200L/Min **BL4040F: 14 Min**  
**BL4080H: 28 Min**

YES

YES

**BL1860B: 1.2 KG**
**BL4040F: 1.8 KG**

0.72 KG

0.8 KG

175 x 76 x 210mm

191 x 86 x 220mm

### SPECIFICATIONS

<b>MAX TEMPERATURE</b>	600°C	
<b>TEMPERATURE ADJUSTMENT</b>	50°C - 600°C WITH 10°C INCREMENTS	
<b>MAX AIR VOLUME</b>	120 / 150 / 180 / 200 L/Min	
<b>CONTINUOUS RUN TIME</b>	600°C/ 200L/Min	<b>BL4040F:</b> 14 Min <b>BL4080H:</b> 28 Min
<b>LOCK ON FUNCTION</b>	YES	
<b>WEIGHT (SKIN)</b>	0.8 KG	
<b>WEIGHT (BATTERY)</b>	<b>BL4040F:</b> 1.8 KG	
<b>DIMENSIONS (LxWxH)</b>	191 x 86 x 220mm	

### HIGHLIGHTS



**CLEAR LCD DISPLAY**  
The LCD display keeps you informed with temperature and air volume settings (both with memory), battery life alerts, and quick error notifications for seamless operation.



**TOOL-LESS NOZZLE CHANGES**  
The quick-release mechanism allows tool-free nozzle removal without touching the hot metal attachments.



**SAFETY**  
Equipped with a lock-off lever and a convenient lock-on button, this tool prioritizes safety without sacrificing performance.



**LED JOB LIGHT**  
Features an LED job light with an after-glow function to effectively illuminate the work area.

### FEATURES

**MAXIMUM HEAT:** Delivering an impressive 600°C, this heat gun outperforms the LXT model's 550°C, giving you the ambient temperature you need for tough jobs.

**TAILORED TEMPERATURE CONTROL:** Fine-tune your heat settings in 10°C increments from 50°C to 600°, ensuring you have the exact temperature for every task.

**VERSATILE 4-STAGE AIR VOLUME:** With four adjustable air volume settings (120, 150, 180, and 200 L/min), you can customize airflow to match your specific needs.

**RUNTIME:** Operate continuously for up to 14 minutes (with 4.0Ah Battery) at 600°C with 200 L/min airflow, giving you the stamina to power through any job.



## INCLUDED ACCESSORIES

**PR00000028**

Glass Protection Nozzle



**PR00000029**

Wide Slot Nozzle



**PR00000030**

Reflector Nozzle



**PR00000031**

20mm Reduction Nozzle



## OPTIONAL ACCESSORIES

**PR00000032**

Overlap Welding Nozzle



**PR00000033**

Solder Sleeves Reflector Nozzle



**PR00000034**

Welding Nozzle



**PR00000039**

Speed Welding Nozzle



**PR00000035**

Pressure Roller



**PR00000041**

Scraper Set

